



Specifications Ledvance LED Floodlight Photocell GEN 3 Black 165W 20000lm 100D - 840 Cool White | IP65 - Light Sensor - Symmetrical

[View Product](#)

General Information

| | |
|--------------------------|----------------------------------|
| SKU | 239244 |
| EAN | 4058075461185 |
| Brand | Ledvance |
| Manufacturer Name | FL PFM165W/4000K SYM100SL BK VS1 |
| Any Lamp all-in warranty | 5 Years |
| Average Lifetime (h) | 70000 |

Technical Information

| | |
|-----------------------------|-----------------|
| Technology | LED Integrated |
| Wattage | 165 |
| Replaces (Watt) | 200 |
| Voltage (V) | 220-240 |
| Dimmable | Not Dimmable |
| Colour Code | 840 Cool White |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra) | 80-89 |
| Colour of Light | White |
| Light colour options | Single Color |
| Luminous Flux (Lumen) | 20000 |
| Luminous Efficacy (lm/W) | 125 |

| | |
|-----------------------|----------------|
| Beam Angle (degree) | 100 |
| Power factor | >0.90 |
| Product Type Category | LED Floodlight |

Fixture Information

| | |
|------------------------|-----------------|
| Mounting Method | Surface |
| Fixture Connection | Cable, 3-pole |
| Optical Cover | Glass |
| Light Distribution | Symmetrical |
| IP-rating | IP65 |
| Impact Protection (IK) | IK08 - 5 joules |
| Operating Temperature | -30 to +50 |
| Colour of the Fixture | Black |
| Housing | Aluminium |
| Colour of material | Black |
| Series | Performance |

Dimensions

| | |
|-------------|-----|
| Length (mm) | 418 |
| Width (mm) | 322 |
| Height (mm) | 60 |

Sensor Information

| | |
|---------------------|--------------|
| Type of sensor | Light Sensor |
| Sensor Time Setting | 15 sec |

Why Any-lamp?



Up to 7 years warranty



Easy return process