



Specifications Philips LED Panel CoreLine RC132V
28,5W 3600lm - 840 Cool White | 120x30cm - UGR <22
- Interact Dimmable

[View Product](#)

General Information

| | |
|--------------------------|-----------------------------------|
| SKU | 246336 |
| EAN | 8719514953659 |
| Brand | Philips |
| Manufacturer Name | RC132V G5 36S/840 WIA W30L120 NOC |
| Any Lamp all-in warranty | 5 Years |
| Average Lifetime (h) | 50000 |
| Series | RC132V |

Technical Information

| | |
|-----------------------------|--------------------------------|
| Technology | LED Integrated |
| Replaces (Watt) | 2x36 |
| Wattage | 28.5 |
| Voltage (V) | 220-240 |
| Dimmable | Dimmable with Philips Interact |
| Colour Code | 840 Cool White |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra) | 80-89 |
| Colour of Light | White |
| Light colour options | Single Color |
| Including bulb | Yes |

| | |
|--------------------------|-------------------------------|
| Amount of bulbs required | 1 |
| Luminous Flux (Lumen) | 3600 |
| Luminous Efficacy (lm/W) | 125 |
| IP-rating | IP20 |
| Impact Protection (IK) | IK03 - 0.35 joule |
| Fixture Connection | PI [Push-in connector 3-pole] |
| Finish of Reflector | Acrylate |
| Power factor | >0.90 |
| Product Type Category | LED Panel |

Fixture Information

| | |
|-----------------------|--------------------------|
| EOC8 | 95365900 |
| Mounting Method | Recessed |
| Unified Glare Rating | < 22 - for general areas |
| Optical Cover | PS (Polystyrene) |
| Operating Temperature | -10 to +40 |
| Emergency Lighting | No Emergency Unit |
| Colour of the Fixture | White |
| Housing | Steel |
| Colour of material | White |

Dimensions

| | |
|----------------|----------|
| LED panel size | 120x30cm |
| Length (mm) | 1195 |
| Width (mm) | 295 |
| Height (mm) | 69 |

Sensor Information

Type of sensor

No Sensor

Why Any-lamp?



Order from the **largest lighting specialist** in Europe



Customised quotation



Up to **7 years warranty**



Easy return process

